



NC 106 Sanding Sealer

Product Data

Description

Oasis Ameron NC 106 is based on alkyd-nitrocellulose combination especially formulated for use on soft , hard wood & wood based materials. It is ideal for the preparation of wood and timber based substrates and can be used with Oasis Ameron NC 108 Lacquer Clear.

Recommended uses

After suitable preparation this product can be applied directly on soft , hard wood & wood based materials.

where wooden grains and transparency is needed.

Principal Properties :

1. Excellent adhesion.
2. Completely fills porosity of the substrate.
3. Fast drying.
4. Gives a good surface for subsequent coats.
5. Easy to apply.
6. Good penetrating properties.

Application methods : Spray

Thin only as required to gain required penetration or suitable spray pattern with NC Thinner upto 50% for use on porous substrates.

Surface Preparation:

Surface to be free of any contamination and free from excessive moisture. Surface shall be sanded and de-dusted.

Physical Data

Volume Solids..... 30% (ASTM D2697)*

Finish..... Matt

Colour..... Clear

Spreading rate.

@ 30 microns DFT 10 m² /Lt

Drying time:

To Touch..... 10 - 20 minutes

To overcoat 3 Hour (Minimum).

- Depending on ambient conditions & surface absorption.

Thinners & Cleaner..... NC Thinner

Flash Point 7°C

Application method Spray

Packing size.....USG

Shelf life 12 months

Storage..... Out of sunlight

Temperature 5°C upto 40°C

Note : Allow for application losses. ie. conditions, surface irregularity, surface porosity and application method.

- * Volume solids is measured in accordance with ASTM-D-2697. Slight variations may occur due to colour and testing variances.