



NC 107 NC Primer

Product Data

Description

Oasis Ameron NC 107 primer is based on alkyd-nitrocellulose combination especially formulated for use on steel, soft, hard wood & wood based materials. Can easily be sanded by wet or dry techniques which will provide a base for optimum gloss development of topcoats

Recommended uses

NC Primer is designed for spray application to clean degrease cold rolled steel and wood. It can be over coated with NC top coats. acrylic lacquers, alkyd high gloss enamels.

Principal Properties :

1. High quality finish
2. Weather resistant
3. Good gloss retention.
4. Good scratch/abrasion resistance.
5. Good flow and drying properties.
6. Simple application

Application methods : Air Spray

Thin only as required to gain required penetration or suitable spray pattern with NC Thinner upto 50% for use on porous substrates.

Surface Preparation:

Surface to be free of any contamination.
Surface shall be sanded and de-dusted.

Physical Data

Volume Solids..... 40% (ASTM D2697)*

FinishSmooth

Colour..... White & Grey

Spreading rate.

@ 30 microns DFT 16 m² /Lt

Drying time:

To Touch..... 10 - 20 minutes

To overcoat 1 hr (Minimum)

- Depending on ambient conditions & surface absorption.

Thinners & Cleaner..... NC Thinner

Flash Point 7°C

Application method Spray

Packing size..... USG - 18 Ltr

Shelf life12 months

Storage.....Out of sunlight

Temperature..... 5°C upto 40°C

Note : Allow for application losses. ie. conditions, surface irregularity, surface porosity and application method.

- * Volume solids is measured in accordance with ASTM-D-2697. Slight variations may occur due to colour and testing variances.